

CBD20-150

电动托盘搬运车 Electric pallet truck

产品性能特点:

货叉进出双面托盘设计;
电子助力转向,轻便、静音;
交流驱动电机,无碳刷、免维护;
电起升,快速、高效,标配起升限位装置;
低能耗,更环保;
交流控制器,无级调速,动力强劲,多重自动保护;
弯道自动减速功能,更安全。
锂电池采用磷酸铁锂电池,充电快,效率高。

Characteristics:

Fork fit for double-deck pallet.
Electronic power steering, light and low noise.
AC driving motor without carbon brush and free maintenance.
Electric lifting, rapid, efficient, electricity limit switch is STD.
Save energy, more environmentally friendly.
AC controller, stepless, strong power, multiple automatic protection.
Curve automatic deceleration function, safer.
The LFP model lithium batteries are fast charging and efficient.



弯道自动减速

AC EPS

高性价比 畅销欧美

选配

Options



170Ah免维护蓄电池+内置充电器;
手柄直立行走功能;

170Ah VRLA Battery + Built-in charger.
Handle upright walking function.

CBD20-150

制造商和技术参数 Manufacturer's Data and Design Characteristics

特性	Feature	单位	
1.1 型号	Model		CBD20
1.2 配置号	Configuration No.		150
1.3 额定载重	Load capacity	kg	2000
1.4 载荷中心距	Load center	mm	600
1.5 轴距	Wheel base	mm	1390
1.6 操作类型	Operating type		步行式 Walkie
车轮			
2.1 轮子类型(前/后)	Wheels type		PU
2.2 驱动轮/平衡轮/承重轮数量	Driving wheel/Balance wheel/Bearing wheel		1/1/4
2.3 驱动轮尺寸	Driving wheel size	mm	Φ248×75
2.4 平衡轮尺寸	Balance wheel size	mm	Φ115×55
2.5 承重轮尺寸	Bearing wheel size	mm	Φ84×80
尺寸			
3.1 货叉最低离地高度	Min.fork lowered height	mm	85
3.2 货叉最大起升高度	Max.fork lifting height	mm	195
3.3 最大起升行程	Max.lifting height	mm	110
3.4 货叉外侧间距	Outside width between forks	mm	540/600/650/685
3.5 货叉内侧间距	Inside width between forks	mm	200/260/310/345
3.6 货叉长度	Fork length	mm	1150/1200
3.7 货叉宽度	Fork width	mm	170
3.8 货叉厚度	Fork thickness	mm	75
3.9 整车全长	Overall length	mm	1750
3.10 车体宽度	Overall width	mm	720
3.11 整车高度(含手柄)	Overall height(With handle)	mm	1385
3.12 整车高度(不含手柄)	Overall height(Without handle)	mm	850
3.13 最小转弯半径	Min.Turning radius	mm	1575
3.14 最小直角堆垛通道宽度 (托盘800×1200, 1200kg货叉放置)	Min.Aisle width for pallets 800×1200	mm	1900
3.15 最小直角堆垛通道宽度 (托盘1000×1200, 1200kg货叉放置)	Min.Aisle width for pallets 1000×1200	mm	1940
性能			
4.1 最大行驶速度, 满载/空载	Travel speed, laden/unladen	km/h	3.5/4
4.2 最大起升速度, 满载/空载	Lift speed, laden/unladen	mm/s	30/35
4.3 最大下降速度, 满载/空载	Lowering speed, laden/unladen	mm/s	40/35
4.4 爬坡度, 满载/空载	Gradeability, laden/unladen	%	6/16
电气配置			
5.1 驱动电机/起升电机	Drive motor/ Lift motor/Steering motor	KW	AC1.5/DC1.2/DC0.15
5.2 制动	Battery voltage / capacity		电磁/再生 Electromagnetic/Regenerative
5.3 电池	Brake		铅酸电池Lead-acid battery 锂电池Lithium battery(optional)
6.1 电池电压/容量	Controller	V/Ah	24/210 24/200
6.2 控制器	Weight		ZAPI ZAPI
6.3 电池重量	Battery weight	kg	192 96
6.4 自重(包含电池)	Service weight with battery	kg	605 509



安徽合力股份有限公司

ANHUI HELI CO., LTD.

地址 / 中国 合肥方兴大道668号

Add / No.668, FangXing Road, Hefei, China

邮编 (Post Code) / 230000

客服热线 (Customer Service Hotline) / 4001-600761

服务电话 (Service Tel) / +86-551-63689000, 63648005

* 本公司保留更改产品设计和规格的权利, 恕不另行通知。

* Our products are subject to improvements and changes without notice.